

| | | | | | |
|--------------------|------------|---|------------|-------------|-----|
| P 513 | Si-Di | =1N4007: 1600V | 31a | BY 228 | 31a |
| P 600 A...M | Si-Di | Gl, 50...1000V, 6A, A=50, B=100, D=200V G=400, J=600, K=800, M=1000V | 31a | BY 329/1200 | 17k |
| P 2221(A) | Si-N | →2N2221(A) | 7a | BC 337 | 7a |
| P 2222(A) | Si-N | →2N2222(A) | 7a | BC 337 | 7a |
| P 2906(A) | Si-P | →2N2906(A) | 7a | BC 327 | 7a |
| P 2907(A) | Si-P | →2N2907(A) | 7a | BC 327 | 7a |
| P 6009 | Si-P-Darl | NF/S-L, 25V, 1A, 5W, B>4000 | 14h | BD 680 | 14h |
| P 6021 | Si-P | ≈BD 166 | 14h | BD 238 | 14h |
| P 7002 | Si-N | ≈BD 400 | 14h | MJE 340 | 14h |
| P 7009 | Si-N-Darl | NF/S-L, 25V, 1A, 5W, B>4000 | 14h | BD 679 | 14h |
| P 7010 | Si-N | ≈BD 139 | 14h | BD 139 | 14h |
| P 7020 | Si-N | ≈BD 135 | 14h | BD 139 | 14h |
| P 7027 | Si-N | ≈BD 135 | 14h | BD 139 | 14h |
| P 7029 | Si-N | ≈BD 410 | 14h | MJE 340 | 14h |
| PA 145 | Si-Di | ≈BA 145 | 31a | BA 159 | 31a |
| PA 148 | Si-Di | ≈BA 148 | 31a | BA 159 | 31a |
| PA 2824 C | Z-IC | +24V | 17b | 7824/TO-220 | 17b |
| PA 7915 C | Z-IC | -15V | 17c | 7915/TO-220 | 17c |
| PBC 107 | Si-N | →BC 107 | 7c | BC 546 | 7a |
| PBC 108 | Si-N | →BC 108 | 7c | BC 546 | 7a |
| PBC 109 | Si-N | →BC 109 | 7c | BC 550 | 7a |
| PBC 182 | Si-N | →BC 182 | 7c | BC 546 | 7a |
| PBC 183 | Si-N | →BC 183 | 7c | BC 546 | 7a |
| PBC 184 | Si-N | →BC 184 | 7c | BC 550 | 7a |
| PBF 259(S) | Si-N | Vid, 300/300V, 0,5A, 0,625W, >40MHz | 7e | BF 420 A | 7c |
| PBF 259 R,RS | Si-N | =PBF 259(S): | 7a | BF 420 A | 7c |
| PBF 493(S) | Si-P | Vid, 300/300V, 0,5A, 0,625W, >50MHz | 7e | BF 421 A | 7c |
| PBF 493 R,RS | Si-P | =PBF 493(S): | 7a | BF 421 A | 7c |
| PC....(NEC) |IC | →µPC.... | | →µPC.... | |
| PC 74 HC00...HCUxx | CMOS-Logic | Standard TTL-Logic(74xx)in CMOS-Techn. | | - | |
| PCA 84 C122... | CMOS-µC-IC | 8-Bit µC, f. FB-Sender, 1kB ROM | | - | |
| PCA 84 C222... | CMOS-µC-IC | 8-Bit µC, f. FB-Sender, 2kB ROM | | - | |
| PCA 84 C422... | CMOS-µC-IC | 8-Bit µC, f. FB-Sender, 4kB ROM | | - | |
| PCA 84 C622... | CMOS-µC-IC | 8-Bit µC, f. FB-Sender, 6kB ROM | | - | |
| PCA 84 C646(P) | CMOS-µC-IC | 8 Bit, Volt. Synth. Tuning, OSD, I ² C | 42-SDIP | - | |
| PCA 84 C822... | CMOS-µC-IC | 8-Bit µC, f. FB-Sender, 8kB ROM | | - | |
| PCA 84 C846(P) | CMOS-µC-IC | 8 Bit, Volt. Synth. Tuning, OSD, I ² C | 42-SDIP | - | |
| PCA 8515(P) | CMOS-IC | Stand-alone On-Screen Display, I ² C-Bus | 24-DIP | - | |
| PCA 8515 T | CMOS-IC | =PCA 8515(P): SMD | 24-MDIP | - | |
| PCA 8516(P) | CMOS-IC | Stand-alone On-Screen Display, I ² C-Bus | 24-DIP | - | |
| PCA 8516 T | CMOS-IC | =PCA 8516(P): SMD | 24-MDIP | - | |
| PCD 8571 D | sRAM-IC | =PCD 8571(P): Keramik | 8-DIC | - | |
| PCD 8571(P) | sRAM-IC | 128x8 Bit, I ² C-Bus | 8-DIP | - | |
| PCD 8571 T | sRAM-IC | =PCD 8571(P): SMD | 8-MDIP | - | |
| PCD 8584(P) | CMOS-IC | I ² C-Bus Controller | 20-DIP | - | |
| PCD 8584 T | CMOS-IC | =PCD 8584(P): SMD | 20-MDIP | - | |
| PCF 29 F64(P) | EEPROM-IC | CMOS, 8k x 8 Bit, Page Erase Option | 28-DIP | - | |
| PCF 29 F64T | EEPROM-IC | =PCF 29F64(P): SMD | 28-MDIP | - | |
| PCF 84 C00B | CMOS-µC-IC | 8 Bit, 256x8Bit RAM, 0kx8Bit ROM, I ² C | 28+28-DIP | - | |
| PCF 84 C20D,P | CMOS-µC-IC | 8 Bit, 64x8Bit RAM, 2kx8Bit ROM, I ² C | 28-DIC/DIP | - | |
| PCF 84 C21(AP) | CMOS-µC-IC | 8 Bit, 64x8Bit RAM, 2kx8Bit ROM, I ² C | 28-DIP | - | |
| PCF 84 C40D,P | CMOS-µC-IC | 8 Bit, 128x8Bit RAM, 4kx8Bit ROM, I ² C | 28-DIC/DIP | - | |
| PCF 84 C41(A)P | CMOS-µC-IC | 8 Bit, 128x8Bit RAM, 4kx8Bit ROM, I ² C | 28-DIP | - | |
| PCF 84 C81P | CMOS-µC-IC | 8 Bit, 256x8Bit RAM, 8kx8Bit ROM, I ² C | 28-DIP | - | |